

屋内照明器具特性

品番 (品名)	LGWC47120														
光源	LLD2000MLCB1 ×1 531.0 lm														
管理番号	K0176342(0)DR1														
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2														

器具効率	62%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	62%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25		
		0.8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32		
		1.0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37		
		1.25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41		
下方投影面積	c m ²	1.5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44		
		2.0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48		
取付高さ	器具間隔最大限		2.5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	51		
	横方向 (A)	縦方向 (B)	3.0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52	
H m	1.17H m	1.17H m	4.0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55	
			5.0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56	
			7.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	58	
			10.0	66	65	64	63	65	64	63	63	63	62	62	62	61	61	60	60	59	

