

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 2 0
光源	LLD2020LCB1 ×1 460.0 l m
管理番号	K0176348 (0) DR 1
B Z 分類	B Z 1

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	91 %		室指数	照明率 (X 0 . 0 1)																Z C M
保守率	良 0.63	0.6	0.6	77	72	69	66	77	72	69	66	76	71	68	66	75	71	68	66	65
	中 0.6	0.8	0.8	83	78	75	72	82	78	75	72	81	77	74	72	79	76	74	72	71
	否 0.56	1.0	1.0	86	82	79	76	85	81	78	76	84	80	78	76	82	79	77	76	74
下方投影面積	c m ²	1.25	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77	
		1.5	90	87	84	82	89	86	84	82	88	85	83	82	86	84	82	81	80	
等価発光面積	c m ²	2.0	92	90	88	86	92	89	87	85	90	88	86	85	88	87	85	84	82	
		2.5	94	92	90	88	93	91	89	88	91	89	88	87	89	88	87	86	84	
取付高さ	器具間隔最大限		3.0	95	93	91	90	94	92	90	89	92	90	89	88	90	89	88	87	85
H m	横方向 (A)	縦方向 (B)	4.0	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	89	86
	0.41 H m	0.41 H m	5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	90	87
			7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	91	88
			10.0	98	97	96	96	97	96	95	95	95	94	94	93	93	92	92	92	89

