

# 屋内照明器具特性

品番 (品名)	NTN88007W														
光源	LLD2000LCS1 ×1                      580.0 1 m														
管理番号	K0183282 ( 0 ) DR 1														
BZ分類	BZ4														

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	57 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	3.4	2.7	2.3	2.0	3.3	2.7	2.3	2.0	3.2	2.6	2.3	2.0	3.1	2.6	2.3	2.0	1.9		
		0.8	4.0	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.6	3.2	2.9	2.6	2.5		
		1.0	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	4.1	3.6	3.3	3.0	3.9	3.6	3.3	3.0	2.9		
		1.25	4.7	4.2	3.8	3.5	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	4.3	3.9	3.6	3.4	3.3		
下方投影面積	c m <sup>2</sup>	1.5	4.9	4.4	4.1	3.8	4.8	4.4	4.0	3.8	4.6	4.3	4.0	3.7	4.5	4.2	3.9	3.7	3.6		
		2.0	5.2	4.8	4.5	4.2	5.1	4.7	4.5	4.2	4.9	4.6	4.4	4.2	4.8	4.5	4.3	4.1	4.0		
取付高さ	器具間隔最大限		2.5	5.4	5.0	4.8	4.5	5.3	5.0	4.7	4.5	5.1	4.9	4.6	4.5	5.0	4.8	4.6	4.4	4.3	
	横方向 (A)	縦方向 (B)	3.0	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.8	4.7	5.1	4.9	4.8	4.6	4.5	
H m	1.27 H m	1.27 H m	4.0	5.6	5.4	5.2	5.1	5.6	5.4	5.2	5.0	5.4	5.2	5.1	4.9	5.3	5.1	5.0	4.9	4.7	
			5.0	5.7	5.6	5.4	5.2	5.7	5.5	5.3	5.2	5.5	5.4	5.2	5.1	5.4	5.3	5.1	5.0	4.9	
			7.0	5.8	5.7	5.6	5.5	5.8	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.1	
			10.0	5.9	5.8	5.7	5.7	5.9	5.8	5.7	5.6	5.7	5.6	5.6	5.5	5.6	5.5	5.5	5.4	5.2	

