

# 屋内照明器具特性

品番 (品名)	NTN88007B	
光源	LLD2000LCB1 ×1	531.0 lm
管理番号	K0179470(0)DR1	
BZ分類	BZ4/1.1/BZ3/3.5/BZ4	

器具効率	62%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	62%	床	10%				10%				10%				10%				0%	
室指数	照明率 (×0.01)																			ZCM
保守率	良	0.67	0.6	3.7	3.0	2.6	2.2	3.6	3.0	2.5	2.2	3.5	2.9	2.5	2.2	3.4	2.9	2.5	2.2	2.1
	中	0.63	0.8	4.4	3.7	3.3	3.0	4.3	3.7	3.3	2.9	4.1	3.6	3.2	2.9	4.0	3.5	3.2	2.9	2.8
	否	0.56	1.0	4.8	4.2	3.8	3.5	4.7	4.2	3.7	3.4	4.5	4.1	3.7	3.4	4.4	4.0	3.6	3.4	3.3
			1.25	5.2	4.6	4.2	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.1	3.9	4.7	4.4	4.1	3.8	3.7
下方投影面積	cm <sup>2</sup>		1.5	5.4	4.9	4.6	4.3	5.3	4.9	4.5	4.2	5.1	4.8	4.5	4.2	5.0	4.7	4.4	4.2	4.0
等価発光面積	cm <sup>2</sup>		2.0	5.7	5.3	5.0	4.8	5.6	5.3	5.0	4.7	5.5	5.1	4.9	4.7	5.3	5.0	4.8	4.6	4.5
取付高さ	器具間隔最大限		2.5	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.0	5.7	5.4	5.2	5.0	5.5	5.3	5.1	4.9	4.8
	横方向 (A)	縦方向 (B)	3.0	6.0	5.8	5.5	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.2	5.6	5.4	5.3	5.1	5.0
Hm	1.29Hm	1.29Hm	4.0	6.2	6.0	5.8	5.6	6.1	5.9	5.7	5.6	6.0	5.8	5.6	5.5	5.8	5.7	5.5	5.4	5.2
			5.0	6.3	6.1	6.0	5.8	6.2	6.1	5.9	5.8	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.4
			7.0	6.4	6.3	6.2	6.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.0	5.9	5.9	5.8	5.6
			10.0	6.5	6.4	6.3	6.2	6.4	6.3	6.3	6.2	6.3	6.2	6.1	6.1	6.1	6.1	6.0	6.0	5.8

