

# 屋内照明器具特性

品番 (品名)	NTN88007B				
光源	LLD4000LCB1 ×1                      845.0 lm				
管理番号	K0179469(0)DR1				
BZ分類	BZ4/1.1/BZ3/3.5/BZ4				

器具効率	54%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	0% 54%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	33	26	22	20	32	26	22	20	31	25	22	19	30	25	22	19	18	
		0.8	38	33	29	26	38	32	28	26	36	31	28	26	35	31	28	25	24	
		1.0	42	37	33	30	41	36	33	30	40	35	32	30	38	35	32	30	29	
		1.25	45	41	37	34	44	40	37	34	43	39	36	34	41	38	36	34	33	
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	47	43	40	37	46	43	40	37	45	42	39	37	43	41	38	36	35	
		2.0	50	47	44	42	49	46	44	41	48	45	43	41	46	44	42	40	39	
取付 高さ	器具間隔最大限		2.5	52	49	46	44	51	48	46	44	49	47	45	44	48	46	44	43	42
	横方向 (A) 縦方向 (B)	3.0	53	50	48	46	52	50	48	46	51	49	47	45	49	48	46	45	44	
H <sub>m</sub>	1.29H <sub>m</sub>	1.29H <sub>m</sub>	4.0	54	52	51	49	54	52	50	49	52	51	49	48	51	50	48	47	46
			5.0	55	54	52	51	55	53	52	50	53	52	51	50	52	51	50	49	47
			7.0	56	55	54	53	56	54	53	52	54	53	52	52	53	52	51	51	49
			10.0	57	56	55	55	56	56	55	54	55	54	54	53	54	53	53	52	50

