

屋内照明器具特性	
品番 (品名)	NTN88007B
光源	LLD2000LCS1 ×1                      580.0 l m
管理番号	K0183285 ( 0 ) DR 1
B Z 分類	BZ3

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM	
下方光束	53 %																			
保守率	良	0.67	0.6	3.3	2.7	2.4	2.1	3.3	2.7	2.4	2.1	3.1	2.7	2.3	2.1	3.0	2.6	2.3	2.1	2.0
	中	0.63	0.8	3.9	3.3	3.0	2.7	3.8	3.3	2.9	2.7	3.7	3.2	2.9	2.7	3.5	3.2	2.9	2.7	2.6
	否	0.56	1.0	4.2	3.7	3.4	3.1	4.1	3.7	3.3	3.1	4.0	3.6	3.3	3.1	3.9	3.5	3.3	3.0	2.9
			1.25	4.5	4.1	3.7	3.5	4.4	4.0	3.7	3.5	4.3	3.9	3.7	3.4	4.1	3.8	3.6	3.4	3.3
下方投影面積	c m <sup>2</sup>	1.5	4.7	4.3	4.0	3.8	4.6	4.3	4.0	3.7	4.5	4.2	3.9	3.7	4.3	4.1	3.9	3.7	3.6	
		2.0	5.0	4.6	4.4	4.2	4.9	4.6	4.3	4.1	4.7	4.5	4.3	4.1	4.6	4.4	4.2	4.0	3.9	
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.2
	横方向 ( A )	縦方向 ( B )	3.0	5.2	5.0	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.3
H m	1.18 H m	1.18 H m	4.0	5.4	5.2	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.6
			5.0	5.4	5.3	5.2	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7
			7.0	5.5	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.3	5.2	5.2	5.1	5.2	5.1	5.1	5.0	4.9
			10.0	5.6	5.5	5.5	5.4	5.5	5.5	5.4	5.3	5.4	5.3	5.3	5.2	5.3	5.2	5.2	5.1	5.0

