

# 屋内照明器具特性

品番 (品名)	XSLA100V														
光源	LLD2000VSCE1 ×1 531.0 lm														
管理番号	K0175638(0)DR1														
BZ分類	BZ5/0.7/BZ4														

器具効率	90%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	90%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	53	42	35	30	51	41	35	30	49	40	34	30	47	39	34	30	28		
		0.8	62	52	45	40	61	51	45	40	58	50	44	40	56	49	43	39	38		
		1.0	68	59	52	47	67	58	52	47	64	57	51	47	62	55	50	46	44		
		1.25	73	65	59	54	72	64	58	54	69	63	58	53	67	61	57	53	51		
下方投影面積	c m <sup>2</sup>	1.5	77	70	64	59	76	69	63	59	73	67	62	58	71	65	61	58	56		
		2.0	82	76	71	67	81	75	70	66	78	73	69	66	76	71	68	65	63		
取付高さ	器具間隔最大限		2.5	85	80	76	72	84	79	75	71	81	77	74	70	79	75	72	70	67	
	横方向 (A)	縦方向 (B)	3.0	87	83	79	76	86	82	78	75	83	80	77	74	81	78	75	73	71	
H m	1.27 H m	1.27 H m	4.0	90	86	83	80	89	85	82	80	86	83	81	79	84	82	79	78	75	
			5.0	92	89	86	84	90	88	85	83	88	86	84	82	86	84	82	80	78	
			7.0	93	91	89	87	92	90	88	87	90	88	87	85	88	86	85	84	81	
			10.0	95	93	92	90	94	92	91	89	91	90	89	88	89	88	87	86	84	

