

# 屋内照明器具特性

品番(品名)	S C 4 3 1	
光源	LDA3L-E17/C/W ×1	280.0 lm
管理番号	K0158274(0)DB1	
BZ分類	BZ10	

器具効率	84%	天井	80%				70%				50%				30%				0%	
	上方光束		49%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	35%	床	10%				10%				10%				10%				0%	
保守率	良 中 否	0.63 0.6 0.56	室指数	照明率 ( X0.01 )																ZCM
下方投影面積 等価発光面積	cm <sup>2</sup>		0.6	35	25	18	13	32	22	16	12	25	17	13	9	18	13	9	6	2
取付高さ Hm	器具間隔最大限		0.8	42	31	24	19	37	28	22	17	29	22	17	13	22	17	13	10	3
	横方向(A)	縦方向(B)	1.0	47	36	29	24	42	33	26	21	33	26	21	17	25	19	15	12	5
Hm	0.00Hm	0.00Hm	1.25	51	41	34	29	46	37	31	26	36	30	25	20	27	22	18	15	7
			1.5	54	45	38	33	49	41	35	30	39	33	28	24	29	25	21	18	8
			2.0	59	51	45	39	53	46	40	36	42	37	32	29	32	28	25	22	11
			2.5	62	55	49	44	56	50	45	40	45	40	36	32	35	31	28	25	13
			3.0	64	58	52	48	58	53	48	43	47	43	39	35	36	33	30	27	15
			4.0	68	62	57	53	61	57	52	49	50	46	43	40	39	36	33	31	18
			5.0	70	65	61	57	63	59	56	52	52	48	45	43	40	38	36	34	20
			7.0	72	68	65	62	66	63	60	57	54	51	49	47	43	41	39	37	23
			10.0	74	71	69	66	68	65	63	61	56	54	52	50	44	43	42	40	25

