

屋内照明器具特性

品番 (品名)	NNQ35452	
光源	LED2700_85_4200 ×1	4200.0lm
管理番号	K0174711(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%																						
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																							
上方光束	0%	反射率	10%				10%				10%				10%				0%																						
下方光束	100%		室指数																																						
		照明率 (X0.01)																				ZCM																			
保守率	良	0.81	0.6	80	73	68	65	79	73	68	65	78	72	68	65	76	71	68	65	64																					
	中	0.77	0.8	87	81	77	74	87	81	77	74	85	80	76	74	83	79	76	73	72																					
	否	0.68	1.0	92	86	83	80	91	86	82	79	89	85	82	79	87	84	81	79	77																					
下方投影面積	等価発光面積	cm ²	1.25	95	91	87	84	94	90	87	84	92	89	86	84	91	88	85	83	82																					
			1.5	98	94	90	88	97	93	90	87	95	91	89	87	93	90	88	86	85																					
取付高さ	器具間隔最大限		2.0	101	97	94	92	99	96	94	92	97	95	93	91	96	93	92	90	88																					
	横方向 (A)	縦方向 (B)	2.5	102	99	97	95	101	99	96	95	99	97	95	93	97	95	94	92	91																					
Hm	0.75Hm	0.75Hm	3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92																					
			4.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94																					
			5.0	106	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95																					
			7.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	99	97																					
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98																					

