

屋内照明器具特性	
品番 (品名)	LGB15111WF
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0111933(2)DB1
BZ分類	BZ7

器具効率	84%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	29%	床	10%				10%				10%				10%				0%				
下方光束	55%	室指数	照明率 (X0.01)																				ZCM
保守率	良 0.63 中 0.6 否 0.56	0.6	40	29	23	18	37	28	21	17	32	25	19	15	28	22	17	14	10				
		0.8	47	37	30	25	44	35	28	23	38	31	25	21	33	27	22	19	14				
		1.0	52	42	35	30	49	40	33	28	43	35	30	26	37	31	26	23	18				
		1.25	57	48	41	35	53	45	39	34	47	40	35	30	40	35	31	27	21				
下方投影面積	c m ²	1.5	60	52	45	40	57	49	43	38	49	43	38	34	43	38	34	30	24				
		2.0	65	58	51	46	61	54	49	44	54	48	44	40	47	42	39	35	28				
取付高さ	器具間隔最大限		2.5	68	62	56	51	64	58	53	49	56	52	47	44	49	45	42	39	31			
	横方向 (A)	縦方向 (B)	3.0	70	64	59	55	66	61	56	52	59	54	50	47	51	48	45	42	34			
H m	1.41 H m	1.41 H m	4.0	73	68	64	60	69	65	61	57	61	58	54	51	54	51	48	46	37			
			5.0	75	71	67	64	71	67	64	61	63	60	57	55	56	53	51	49	40			
			7.0	78	74	71	68	73	70	68	65	65	63	61	59	58	56	54	52	43			
			10.0	79	77	74	72	75	73	71	69	67	65	64	62	60	58	57	55	46			

