

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 1 2 U
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0175941 (0) DR 1
B Z 分類	B Z 7

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	35 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	27 %	室指数	照明率 (X0.01) Z C M																			
保守率	良 中 否 0.63 0.6 0.56	0.6	28	21	16	13	26	19	15	12	21	16	12	10	16	12	10	8	4			
		0.8	33	26	21	18	30	24	20	16	25	20	16	14	19	16	13	11	6			
		1.0	37	30	25	22	34	28	23	20	27	23	19	17	21	18	15	13	8			
		1.25	41	34	29	26	37	31	27	24	30	26	22	20	24	20	18	16	10			
下方投影面積	c m ²	1.5	43	37	32	29	39	34	30	27	32	28	25	22	25	22	20	18	11			
		2.0	46	41	37	34	42	38	34	31	35	31	28	26	27	25	23	21	13			
取付高さ	器具間隔最大限		2.5	49	44	40	37	44	40	37	34	36	33	31	29	29	27	25	15			
	横方向 (A)	縦方向 (B)	3.0	50	46	43	40	46	42	39	37	38	35	33	31	30	28	26	16			
1.5 m	2.55 m	2.01 m	4.0	52	49	46	43	48	45	42	40	39	37	35	33	32	30	27	18			
2	3.39	2.66	5.0	53	51	48	46	49	47	44	42	41	39	37	35	33	31	30	19			
2.5	4.22	3.31	7.0	55	53	51	49	50	49	47	45	42	40	39	38	34	33	32	20			
3	5.07	3.98	10.0	56	55	53	52	52	50	49	48	43	42	41	40	35	34	33	22			

