

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 2 3 S U
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 6 0 3 4 6 ( 0 ) D R 1
B Z 分類	B Z 1 0

器具効率	40 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	19 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	21 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 ( X 0 . 0 1 )																Z C M	
保守率	良	0.63	0.6	1.7	1.2	8	6	1.5	1.1	8	5	1.2	9	6	4	1.0	7	5	3	1
	中	0.6	0.8	2.0	1.5	1.1	9	1.8	1.4	1.0	8	1.5	1.1	8	6	1.2	9	7	5	2
	否	0.56	1.0	2.2	1.7	1.4	1.1	2.0	1.6	1.3	1.0	1.7	1.3	1.0	8	1.3	1.0	8	6	3
			1.25	2.5	2.0	1.6	1.3	2.2	1.8	1.5	1.2	1.8	1.5	1.2	1.0	1.4	1.2	1.0	8	4
下方投影面積		cm <sup>2</sup>	1.5	2.6	2.2	1.8	1.5	2.4	2.0	1.7	1.4	2.0	1.6	1.4	1.2	1.6	1.3	1.1	9	5
等価発光面積		cm <sup>2</sup>	2.0	2.9	2.5	2.1	1.9	2.6	2.3	2.0	1.7	2.2	1.9	1.6	1.4	1.7	1.5	1.3	1.2	7
取付高さ	器具間隔最大限		2.5	3.0	2.7	2.4	2.1	2.8	2.5	2.2	2.0	2.3	2.0	1.8	1.6	1.9	1.7	1.5	1.3	8
	横方向 (A)	縦方向 (B)	3.0	3.1	2.8	2.5	2.3	2.9	2.6	2.3	2.1	2.4	2.2	2.0	1.8	1.9	1.8	1.6	1.5	1.0
H <sub>m</sub>	0.00H <sub>m</sub>	0.00H <sub>m</sub>	4.0	3.3	3.0	2.8	2.6	3.0	2.8	2.6	2.4	2.5	2.3	2.2	2.0	2.1	1.9	1.8	1.7	1.1
			5.0	3.4	3.2	2.9	2.7	3.1	2.9	2.7	2.6	2.6	2.5	2.3	2.2	2.2	2.0	1.9	1.8	1.2
			7.0	3.5	3.3	3.2	3.0	3.2	3.1	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.2	2.1	2.0	1.4
			10.0	3.6	3.5	3.3	3.2	3.3	3.2	3.1	3.0	2.8	2.7	2.6	2.6	2.4	2.3	2.2	2.1	1.5

