

屋内照明器具特性

品番 (品名)	L S E W6 0 0 8 Y									
光源	LED2700_70_400 x1					400.0 l m				
管理番号	K0170953 (0) DR 1									
B Z 分類	B Z 3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																					
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																					
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %																					
下方光束	100 %	室指数	照明率 (X0.01)																Z C M																					
保守率	良	0.69	0.6	62	51	44	39	61	51	44	39	59	50	43	39	57	49	43	39	37																				
	中	0.67	0.8	72	62	55	50	71	61	55	50	68	60	54	50	66	59	53	49	47																				
	否	0.63	1.0	78	69	63	57	77	68	62	57	74	67	61	57	72	66	61	57	55																				
			1.25	84	76	70	65	83	75	69	64	80	73	68	64	77	72	67	64	61																				
下方投影面積			c m ²		1.5		88		80		75		70		86		79		74		70		84		78		73		69		81		76		72		68		66	
等価発光面積			c m ²		2.0		93		87		82		77		91		86		81		77		88		84		80		76		86		82		78		75		73	
取付高さ	器具間隔最大限		2.5		96		91		86		82		94		90		85		82		92		88		84		81		89		86		83		80		78			
	横方向 (A)	縦方向 (B)	3.0		98		93		89		86		96		92		89		86		94		90		87		84		91		88		86		83		81			
H m	1.13 H m	1.13 H m	4.0		100		97		94		91		99		96		93		90		96		94		91		89		94		92		90		88		85			
			5.0		102		99		96		94		101		98		96		93		98		96		94		92		96		94		92		90		88			
			7.0		104		102		100		98		102		100		99		97		100		98		97		95		98		96		95		94		91			
			10.0		105		104		102		101		104		102		101		100		101		100		99		98		99		98		97		96		93			

