

屋内照明器具特性

品番 (品名)	NNQ35759	
光源	LED3000_85_5200 ×1	5200.0 lm
管理番号	K0174717(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	90	86	83	81	90	85	83	81	89	85	82	80	88	84	82	80	79
	中	0.77	0.8	95	91	88	86	94	90	88	86	93	90	87	86	92	89	87	85	84
	否	0.68	1.0	98	94	91	89	97	94	91	89	96	93	91	89	94	92	90	89	87
下方投影面積 等価発光面積	cm ²	1.25	1.00	97	94	92	99	96	94	92	98	95	93	92	96	94	93	91	90	
		1.5	1.01	99	96	95	101	98	96	94	99	97	95	94	97	96	94	93	91	
		2.0	1.03	101	99	97	102	100	98	97	101	99	97	96	99	97	96	95	94	
取付高さ	器具間隔最大限		2.5	1.04	102	101	99	103	102	100	99	101	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	1.05	103	102	101	104	102	101	100	102	101	100	99	100	99	98	98	96
Hm	0.78Hm	0.78Hm	4.0	1.06	105	103	102	105	104	103	102	103	102	101	100	101	100	100	99	97
			5.0	1.06	105	104	103	105	104	103	103	103	103	102	101	101	101	100	100	97
			7.0	1.07	106	105	105	106	105	105	104	104	103	103	102	102	101	101	101	98
			10.0	1.08	107	106	106	106	106	105	105	104	104	103	103	102	102	102	101	99

