

屋内照明器具特性	
品番(品名)	XY2889K
光源	LDT6L-G-E17/S/T6 ×1 810.0lm
管理番号	K0176850(2)DR1
BZ分類	BZ10

器具効率	60%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	30%	床	10%				10%				10%				10%				0%	
下方光束	30%		照明率 (X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	2.5	1.7	1.2	0.9	2.3	1.6	1.1	0.8	1.8	1.3	0.9	0.6	1.4	1.0	0.7	0.4	0.1	
		0.8	3.0	2.2	1.7	1.3	2.7	2.0	1.5	1.1	2.2	1.6	1.2	0.9	1.7	1.3	0.9	0.7	0.3	
		1.0	3.3	2.6	2.0	1.6	3.0	2.3	1.8	1.5	2.4	1.9	1.5	1.2	1.9	1.5	1.2	0.9	0.4	
		1.25	3.7	2.9	2.4	2.0	3.3	2.7	2.2	1.8	2.7	2.2	1.8	1.5	2.1	1.7	1.4	1.1	0.6	
下方投影面積	cm ²	1.5	3.9	3.2	2.7	2.3	3.6	2.9	2.5	2.1	2.9	2.4	2.0	1.7	2.3	1.9	1.6	1.3	0.7	
		2.0	4.3	3.7	3.2	2.7	3.9	3.3	2.9	2.5	3.2	2.8	2.4	2.1	2.5	2.2	1.9	1.7	1.0	
取付高さ	器具間隔最大限		2.5	4.5	4.0	3.5	3.1	4.1	3.6	3.2	2.9	3.4	3.0	2.7	2.4	2.7	2.4	2.2	1.9	1.2
	横方向(A)	縦方向(B)	3.0	4.7	4.2	3.8	3.4	4.3	3.8	3.5	3.1	3.5	3.2	2.9	2.6	2.9	2.6	2.3	2.1	1.3
Hm	0.00Hm	0.00Hm	4.0	4.9	4.5	4.1	3.8	4.5	4.1	3.8	3.5	3.8	3.5	3.2	3.0	3.1	2.8	2.6	2.4	1.6
			5.0	5.0	4.7	4.4	4.1	4.7	4.3	4.0	3.8	3.9	3.6	3.4	3.2	3.2	3.0	2.8	2.6	1.8
			7.0	5.2	4.9	4.7	4.4	4.8	4.6	4.3	4.1	4.1	3.9	3.7	3.5	3.4	3.2	3.0	2.9	2.0
			10.0	5.4	5.2	5.0	4.8	5.0	4.8	4.6	4.4	4.2	4.1	3.9	3.8	3.5	3.4	3.3	3.1	2.2

