

屋内照明器具特性	
品番 (品名)	NNF W2 1 8 0 3 K
光源	LED3000_85_910 x1 910.0 l m
管理番号	K0175591 (0) DR 1
B Z 分類	BZ6 / 1.4 / BZ5 / 2.3 / BZ6

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	20 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	80 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	19
	中	0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	48	41	35	31	27
	否	0.77	1.0	67	56	48	42	64	54	46	41	59	50	44	39	54	46	41	37	32
			1.25	73	63	55	49	70	60	53	47	64	56	50	45	58	52	47	43	38
下方投影面積		cm ²	1.5	77	68	60	54	74	65	58	53	68	60	55	50	62	56	51	47	42
等価発光面積		cm ²	2.0	83	75	68	62	79	72	66	61	73	67	62	57	67	62	58	54	48
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	76	71	66	76	71	67	62	70	66	62	59	52
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	86	80	75	70	79	74	70	66	73	69	66	63	56
1.5m	2.13 m	1.92 m	4.0	92	87	83	78	89	84	80	76	82	78	75	72	76	73	70	68	60
2	2.84	2.54	5.0	94	90	86	82	91	87	83	80	84	81	78	75	78	75	73	71	63
2.5	3.57	3.16	7.0	97	93	90	87	93	90	88	85	87	84	82	80	81	79	77	75	67
3	4.26	3.78	10.0	99	96	94	92	95	93	91	89	89	87	85	84	83	81	80	78	70

