

# 屋内照明器具特性

品番 (品名)	NNF W2 1 8 1 0 C									
光源	LED5000_85_1480 x1					1480.0 lm				
管理番号	K0175590 (2) DR 1									
BZ分類	BZ6/1.4/BZ5/2.3/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	19%	反射率	床	10%				10%				10%				10%				0%
下方光束	81%		室指数	照明率 ( X0.01 )																ZCM
保守率	良 中 否 0.83 0.81 0.77	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	19	
		0.8	61	49	41	35	58	47	40	34	53	44	37	32	48	41	35	31	27	
		1.0	67	56	48	42	64	54	46	41	59	50	44	39	54	46	41	37	32	
		1.25	73	63	55	49	70	60	53	47	64	56	50	45	59	52	47	43	38	
下方投影面積	c m <sup>2</sup>	1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	51	47	42	
		2.0	83	75	68	62	79	72	66	61	73	67	62	57	67	62	58	54	48	
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	77	71	66	77	71	67	63	70	66	62	59	53
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	86	80	75	70	79	74	70	66	73	69	66	63	56
1.5m	2.15 m	1.93 m	4.0	92	87	83	79	89	84	80	76	82	78	75	72	76	73	70	68	61
2	2.86	2.55	5.0	94	90	86	83	91	87	83	80	84	81	78	75	78	76	73	71	64
2.5	3.59	3.16	7.0	97	94	90	88	93	90	88	85	87	84	82	80	81	79	77	75	67
3	4.28	3.77	10.0	99	96	94	92	95	93	91	89	89	87	85	84	83	81	80	78	71

