

屋内照明器具特性	
品番 (品名)	NNFS 2 1 8 1 2 C
光源	LED5000_85_1470 x1 1470.0 lm
管理番号	K0175588 (0) DR 1
BZ分類	BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	19 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	81 %	室指数	照明率 ( X0.01) ZCM																			
保守率	良	0.83	0.6	5.2	3.9	3.1	2.6	4.9	3.8	3.0	2.5	4.5	3.5	2.9	2.4	4.1	3.3	2.7	2.3	2.0		
	中	0.81	0.8	6.1	4.9	4.1	3.5	5.8	4.7	4.0	3.4	5.3	4.4	3.7	3.2	4.9	4.1	3.5	3.1	2.7		
	否	0.77	1.0	6.7	5.6	4.8	4.2	6.4	5.4	4.7	4.1	5.9	5.0	4.4	3.9	5.4	4.7	4.1	3.7	3.2		
			1.25	7.3	6.3	5.5	4.9	7.0	6.1	5.3	4.8	6.4	5.6	5.0	4.5	5.9	5.2	4.7	4.3	3.8		
下方投影面積		cm <sup>2</sup>	1.5	7.7	6.8	6.0	5.4	7.4	6.5	5.8	5.3	6.8	6.1	5.5	5.0	6.2	5.6	5.2	4.7	4.2		
等価発光面積		cm <sup>2</sup>	2.0	8.3	7.5	6.8	6.3	8.0	7.2	6.6	6.1	7.3	6.7	6.2	5.8	6.7	6.2	5.8	5.4	4.8		
取付高さ	器具間隔最大限		2.5	8.7	7.9	7.3	6.8	8.3	7.7	7.1	6.6	7.7	7.1	6.7	6.3	7.1	6.6	6.3	5.9	5.3		
	横方向 (A)	縦方向 (B)	3.0	8.9	8.3	7.7	7.3	8.6	8.0	7.5	7.1	7.9	7.5	7.0	6.7	7.3	6.9	6.6	6.3	5.6		
1.5m	2.15m	1.93m	4.0	9.2	8.7	8.3	7.9	8.9	8.4	8.0	7.6	8.3	7.9	7.5	7.2	7.6	7.3	7.0	6.8	6.1		
2	2.86	2.54	5.0	9.5	9.0	8.6	8.3	9.1	8.7	8.4	8.0	8.5	8.1	7.8	7.6	7.8	7.6	7.3	7.1	6.4		
2.5	3.59	3.16	7.0	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.5	8.7	8.5	8.2	8.0	8.1	7.9	7.7	7.5	6.8		
3	4.28	3.76	10.0	9.9	9.6	9.4	9.2	9.6	9.3	9.1	8.9	8.9	8.7	8.5	8.4	8.3	8.2	8.0	7.9	7.1		

