

屋内照明器具特性

品番 (品名)	NNFS 2 1 8 3 0 C									
光源	LED3000_85_1390 ×1					1390.0 lm				
管理番号	K0175588 (0) DR 1									
B Z 分類	BZ6 / 1.1 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 6.0 / BZ6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束		19 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
	下方光束		81 %		10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	20		
	中	0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	49	41	35	31	27		
	否	0.77	1.0	67	56	48	42	64	54	47	41	59	50	44	39	54	47	41	37	32		
			1.25	73	63	55	49	70	61	53	48	64	56	50	45	59	52	47	43	38		
下方投影面積	c m ²		1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	52	47	42		
	等価発光面積		c m ²	2.0	83	75	68	63	80	72	66	61	73	67	62	58	67	62	58	54	48	
取付高さ	器具間隔最大限		2.5	87	79	73	68	83	77	71	66	77	71	67	63	71	66	63	59	53		
	横方向 (A)	縦方向 (B)	3.0	89	83	77	73	86	80	75	71	79	75	70	67	73	69	66	63	56		
1.5m	2.15 m	1.93 m	4.0	92	87	83	79	89	84	80	76	83	79	75	72	76	73	70	68	61		
2	2.86	2.54	5.0	95	90	86	83	91	87	84	80	85	81	78	76	78	76	73	71	64		
2.5	3.59	3.16	7.0	97	94	91	88	94	91	88	85	87	85	82	80	81	79	77	75	68		
3	4.28	3.76	10.0	99	96	94	92	96	93	91	89	89	87	85	84	83	82	80	79	71		

