

|          |   |
|----------|---|
| 屋内照明器具特性 |   |
| 品番 (品名)  | NNFS 2 1 8 1 2 C                        |
| 光源       | LED5000_85_1470 x1 1470.0 lm            |
| 管理番号     | K0175588 (0) DR 1                       |
| BZ分類     | BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5<br>/6.0/BZ6 |

|        |                  |         |                  |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |  |  |
|--------|------------------|---------|------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|--|--|
| 器具効率   | 100 %            | 天井      | 80 %             |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |  |  |
|        |                  | 壁       | 70               | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |  |  |
| 上方光束   | 19 %             | 床       | 10 %             |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |  |  |
| 下方光束   | 81 %             | 室指数     | 照明率 ( X0.01) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |  |  |
| 保守率    | 良                | 0.83    | 0.6              | 52 | 39 | 31 | 26   | 49 | 38 | 30 | 25   | 45 | 35 | 29 | 24   | 41 | 33 | 27 | 23  | 20 |  |  |
|        | 中                | 0.81    | 0.8              | 61 | 49 | 41 | 35   | 58 | 47 | 40 | 34   | 53 | 44 | 37 | 32   | 49 | 41 | 35 | 31  | 27 |  |  |
|        | 否                | 0.77    | 1.0              | 67 | 56 | 48 | 42   | 64 | 54 | 47 | 41   | 59 | 50 | 44 | 39   | 54 | 47 | 41 | 37  | 32 |  |  |
|        |                  |         | 1.25             | 73 | 63 | 55 | 49   | 70 | 61 | 53 | 48   | 64 | 56 | 50 | 45   | 59 | 52 | 47 | 43  | 38 |  |  |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 77               | 68 | 60 | 54 | 74   | 65 | 58 | 53 | 68   | 61 | 55 | 50 | 62   | 56 | 52 | 47 | 42  |    |  |  |
|        |                  | 2.0     | 83               | 75 | 68 | 63 | 80   | 72 | 66 | 61 | 73   | 67 | 62 | 58 | 67   | 62 | 58 | 54 | 48  |    |  |  |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 87 | 79 | 73 | 68   | 83 | 77 | 71 | 66   | 77 | 71 | 67 | 63   | 71 | 66 | 63 | 59  | 53 |  |  |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 89 | 83 | 77 | 73   | 86 | 80 | 75 | 71   | 79 | 75 | 70 | 67   | 73 | 69 | 66 | 63  | 56 |  |  |
| 1.5m   | 2.15 m           | 1.93 m  | 4.0              | 92 | 87 | 83 | 79   | 89 | 84 | 80 | 76   | 83 | 79 | 75 | 72   | 76 | 73 | 70 | 68  | 61 |  |  |
| 2      | 2.86             | 2.54    | 5.0              | 95 | 90 | 86 | 83   | 91 | 87 | 84 | 80   | 85 | 81 | 78 | 76   | 78 | 76 | 73 | 71  | 64 |  |  |
| 2.5    | 3.59             | 3.16    | 7.0              | 97 | 94 | 91 | 88   | 94 | 91 | 88 | 85   | 87 | 85 | 82 | 80   | 81 | 79 | 77 | 75  | 68 |  |  |
| 3      | 4.28             | 3.76    | 10.0             | 99 | 96 | 94 | 92   | 96 | 93 | 91 | 89   | 89 | 87 | 85 | 84   | 83 | 82 | 80 | 79  | 71 |  |  |

