

屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 2	
光源	LLD3020LCB1 ×1	795.0 1 m
管理番号	K0176345 (0) DR 1	
B Z 分類	B Z 1	

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	89 %	床	10 %				10 %				10 %				10 %				0 %		
室指数	照明率 (X 0 . 0 1)																			Z C M	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	87	88	90	92	93	94	94	95	95	
	等価発光面積		c m ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	88	88	88	88	88	88	88	88	88	88
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	0.41 H m	0.41 H m	4.0	5.0	7.0	10.0	94	94	95	95	94	94	94	94	94	94	94	94	94	94	

