

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNLK42591J + NEL4400EN       |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3580 x1 3580.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0192610(0)DB1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/0.9/BZ3                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |         |      |                  |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
|--------|---------|---------|------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|----|----|
| 器具効率   | 100%    | 天井      | 80%  |                  |     |     | 70% |     |     |     | 50% |     |    |    | 30% |     |    |    | 0% |    |
|        |         |         | 壁    | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0% |
| 上方光束   | 4%      | 反射率     | 床    | 10%              |     |     |     | 10% |     |     |     | 10% |    |    |     | 10% |    |    |    | 0% |
| 下方光束   | 96%     |         | 室指数  | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
| 保守率    | 良       | 0.81    | 0.6  | 60               | 49  | 42  | 37  | 59  | 48  | 41  | 36  | 56  | 47 | 41 | 36  | 54  | 46 | 40 | 36 | 34 |
|        | 中       | 0.77    | 0.8  | 70               | 60  | 53  | 48  | 69  | 59  | 52  | 47  | 66  | 57 | 51 | 47  | 63  | 56 | 51 | 46 | 44 |
|        | 否       | 0.68    | 1.0  | 77               | 67  | 61  | 56  | 75  | 66  | 60  | 55  | 72  | 65 | 59 | 55  | 69  | 63 | 58 | 54 | 51 |
|        |         |         | 1.25 | 83               | 74  | 68  | 63  | 81  | 73  | 67  | 63  | 78  | 71 | 66 | 62  | 75  | 69 | 65 | 61 | 58 |
| 下方投影面積 |         |         | 1.5  | 87               | 79  | 73  | 68  | 85  | 78  | 72  | 68  | 81  | 75 | 71 | 67  | 78  | 73 | 69 | 66 | 63 |
| 等価発光面積 |         |         | 2.0  | 92               | 85  | 80  | 76  | 90  | 84  | 79  | 75  | 86  | 82 | 78 | 74  | 83  | 79 | 76 | 73 | 70 |
| 取付高さ   | 器具間隔最大限 |         | 2.5  | 95               | 89  | 85  | 81  | 93  | 88  | 84  | 80  | 90  | 85 | 82 | 79  | 86  | 83 | 80 | 77 | 74 |
|        | 横方向 (A) | 縦方向 (B) | 3.0  | 97               | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 92  | 88 | 85 | 82  | 88  | 86 | 83 | 81 | 77 |
| 1.5m   | 1.83m   | 2.16m   | 4.0  | 99               | 96  | 93  | 90  | 98  | 94  | 92  | 89  | 94  | 92 | 89 | 87  | 91  | 89 | 87 | 85 | 82 |
| 2      | 2.42    | 2.71    | 5.0  | 101              | 98  | 95  | 93  | 99  | 97  | 94  | 92  | 96  | 94 | 92 | 90  | 93  | 91 | 89 | 88 | 84 |
| 2.5    | 3.01    | 3.29    | 7.0  | 103              | 101 | 99  | 97  | 101 | 99  | 97  | 96  | 98  | 96 | 95 | 93  | 95  | 94 | 92 | 91 | 87 |
| 3      | 3.6     | 3.88    | 10.0 | 104              | 103 | 101 | 100 | 103 | 101 | 100 | 99  | 99  | 98 | 97 | 96  | 96  | 95 | 94 | 94 | 90 |

