

屋内照明器具特性

品番 (品名)	NNLK42591J + NEL4500HN														
光源	LED5000_85_4560 x1 4560.0 lm														
管理番号	K0192610(0)DB1														
BZ分類	BZ4/0.9/BZ3														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	反射率	床	10%				10%				10%				10%				0%
下方光束	96%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.81	0.6	60	49	42	37	59	48	41	36	56	47	41	36	54	46	40	36	34
		0.77	0.8	70	60	53	48	69	59	52	47	66	57	51	47	63	56	51	46	44
		0.68	1.0	77	67	61	56	75	66	60	55	72	65	59	55	69	63	58	54	51
			1.25	83	74	68	63	81	73	67	63	78	71	66	62	75	69	65	61	58
下方投影面積			1.5	87	79	73	68	85	78	72	68	81	75	71	67	78	73	69	66	63
等価発光面積			2.0	92	85	80	76	90	84	79	75	86	82	78	74	83	79	76	73	70
取付高さ	器具間隔最大限		2.5	95	89	85	81	93	88	84	80	90	85	82	79	86	83	80	77	74
	横方向 (A)	縦方向 (B)	3.0	97	92	88	85	95	91	87	84	92	88	85	82	88	86	83	81	77
1.5m	1.83m	2.16m	4.0	99	96	93	90	98	94	92	89	94	92	89	87	91	89	87	85	82
2	2.42	2.71	5.0	101	98	95	93	99	97	94	92	96	94	92	90	93	91	89	88	84
2.5	3.01	3.29	7.0	103	101	99	97	101	99	97	96	98	96	95	93	95	94	92	91	87
3	3.6	3.88	10.0	104	103	101	100	103	101	100	99	99	98	97	96	96	95	94	94	90

