

# 屋内照明器具特性

|         |                                   |  |  |  |  |
|---------|-----------------------------------|--|--|--|--|
| 品番 (品名) | NNLK42722J + NEL4300CN            |  |  |  |  |
| 光源      | LED5000_85_3100 x1      3100.0 lm |  |  |  |  |
| 管理番号    | K0191891(0)DB1                    |  |  |  |  |
| BZ分類    | BZ5/1.8/BZ4                       |  |  |  |  |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.81            | 0.6           | 57  | 45  | 37  | 31  | 56  | 44  | 37  | 31  | 53  | 43 | 36 | 31  | 51 | 42 | 36 | 31  | 29 |
|        | 中       | 0.77            | 0.8           | 67  | 56  | 48  | 42  | 66  | 55  | 47  | 42  | 63  | 53 | 47 | 42  | 60 | 52 | 46 | 41  | 39 |
|        | 否       | 0.68            | 1.0           | 74  | 63  | 55  | 50  | 72  | 62  | 55  | 50  | 69  | 61 | 54 | 49  | 67 | 59 | 53 | 49  | 47 |
|        |         |                 | 1.25          | 80  | 70  | 63  | 57  | 78  | 69  | 63  | 57  | 75  | 68 | 62 | 57  | 72 | 66 | 61 | 56  | 54 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 84  | 75  | 69  | 63  | 82  | 74  | 68  | 63  | 79  | 72 | 67 | 62  | 77 | 71 | 66 | 62  | 59 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 90  | 83  | 77  | 72  | 88  | 82  | 76  | 71  | 85  | 79 | 75 | 71  | 82 | 78 | 73 | 70  | 67 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 93  | 87  | 82  | 78  | 92  | 86  | 81  | 77  | 89  | 84 | 80 | 76  | 86 | 82 | 78 | 75  | 73 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 96  | 91  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87 | 84 | 80  | 89 | 85 | 82 | 79  | 77 |
| 1.5m   | 2.02m   | 2.12m           | 4.0           | 99  | 95  | 91  | 88  | 97  | 94  | 90  | 87  | 95  | 91 | 89 | 86  | 92 | 89 | 87 | 85  | 82 |
| 2      | 2.66    | 2.67            | 5.0           | 101 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94 | 92 | 89  | 94 | 92 | 90 | 88  | 85 |
| 2.5    | 3.31    | 3.24            | 7.0           | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 97 | 95 | 93 | 92  | 89 |
| 3      | 3.94    | 3.82            | 10.0          | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99 | 98 | 97  | 98 | 97 | 96 | 95  | 92 |

