

屋内照明器具特性

品番 (品名)	XLX440NLWU									
光源	LED4000_85_3520 x1 3520.0 lm									
管理番号	K0144285(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数																			
下方光束	96%	照明率 (X0.01)																			
保守率	良 0.83 中 0.81 否 0.77	0.6	5.7	4.5	3.8	3.2	5.6	4.4	3.7	3.2	5.3	4.3	3.6	3.2	5.0	4.2	3.6	3.1	2.9		
		0.8	6.7	5.6	4.8	4.3	6.5	5.5	4.8	4.2	6.2	5.3	4.7	4.2	5.9	5.1	4.6	4.1	3.9		
		1.0	7.4	6.3	5.6	5.0	7.2	6.2	5.5	5.0	6.8	6.0	5.4	4.9	6.5	5.8	5.3	4.8	4.6		
		1.25	7.9	7.0	6.3	5.7	7.7	6.9	6.2	5.7	7.4	6.6	6.0	5.6	7.1	6.4	5.9	5.5	5.2		
下方投影面積	c m ²	1.5	8.3	7.5	6.8	6.2	8.1	7.3	6.7	6.2	7.8	7.1	6.5	6.1	7.4	6.9	6.4	6.0	5.7		
		2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	7.0	8.3	7.7	7.2	6.8	7.9	7.5	7.1	6.7	6.4		
		2.5	9.2	8.6	8.0	7.6	9.0	8.4	7.9	7.5	8.6	8.1	7.7	7.4	8.3	7.9	7.5	7.2	6.9		
取付高さ	器具間隔最大限		3.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.9	8.4	8.1	7.7	8.5	8.2	7.9	7.6		
	横方向 (A)	縦方向 (B)																			
1.5m	1.96m	2.12m	4.0	9.7	9.3	8.9	8.5	9.5	9.1	8.8	8.4	9.2	8.8	8.5	8.2	8.8	8.6	8.3	8.1		
2	2.59	2.67	5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.0	8.8	8.6	8.4		
2.5	3.23	3.24	7.0	10.1	9.9	9.6	9.3	10.0	9.7	9.5	9.2	9.6	9.4	9.2	9.0	9.3	9.1	8.9	8.8		
3	3.86	3.83	10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.8	9.6	9.8	9.6	9.5	9.3	9.5	9.3	9.2	9.1		

