

# 屋内照明器具特性

品番 (品名)	P M E L C 1 5 5 0 N 1									
光源	LED5000_70_4330 x1					4330.0 lm				
管理番号	K0177910(0)DY1									
BZ分類	BZ2/1.8/BZ3/8.5/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	5%	反射率	床	10%				10%				10%				10%				0%
下方光束	95%		室指数	照明率 ( X0.01 )																ZCM
保守率	良	0.69	0.6	67	58	52	47	66	57	51	47	63	56	50	47	61	54	50	46	44
	中	0.67	0.8	76	67	61	56	74	66	60	56	71	64	59	55	69	63	58	55	53
	否	0.63	1.0	81	73	67	63	79	72	66	62	76	70	65	61	73	68	64	60	58
			1.25	86	78	73	68	84	77	72	68	81	75	70	67	78	73	69	66	63
下方投影面積			1.5	89	82	77	73	87	81	76	72	84	78	74	71	81	76	73	70	67
			2.0	93	87	83	79	91	86	82	78	88	83	80	77	84	81	78	75	72
取付高さ	器具間隔最大限		2.5	96	91	87	83	94	89	86	82	90	86	83	81	87	84	81	79	76
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	95	92	88	85	92	89	86	83	89	86	84	82	78
1.5m	0.94m	2.06m	4.0	100	96	93	91	98	95	92	89	94	92	89	87	91	89	87	85	81
2	1.26	2.55	5.0	101	98	96	93	99	97	94	92	96	93	92	90	92	91	89	87	84
2.5	1.6	3.07	7.0	103	100	99	97	101	99	97	95	97	96	94	93	94	93	91	90	86
3	1.93	3.62	10.0	104	102	101	99	102	101	99	98	99	97	96	95	95	94	93	92	88

