

屋内照明器具特性	
品番 (品名)	P M E L C 1 5 2 7 N 1
光源	LED2700_70_3850 x1 3850.0 lm
管理番号	K0177909 (0) DY 1
B Z 分類	BZ2 / 1.8 / BZ3

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	95 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	68	58	52	48	66	58	52	48	64	56	51	47	62	55	50	47	45			
	中	0.67	0.8	76	67	61	57	75	66	61	57	72	65	60	56	69	63	59	55	53			
	否	0.63	1.0	81	73	68	63	80	72	67	63	77	70	66	62	74	69	65	61	59			
			1.25	86	79	73	69	84	78	73	69	81	76	71	68	78	74	70	67	64			
下方投影面積	c m ²		1.5	89	83	77	73	87	81	77	73	84	79	75	72	81	77	73	70	68			
	等価発光面積		2.0	93	88	83	80	91	86	82	79	88	84	80	77	85	81	78	76	73			
取付高さ	器具間隔最大限		2.5	96	91	87	84	94	90	86	83	91	87	84	81	87	84	82	80	76			
	横方向 (A)	縦方向 (B)	3.0	98	93	90	87	96	92	89	86	92	89	86	84	89	87	84	82	79			
1.5m	0.89 m	2.07 m	4.0	100	97	94	91	98	95	92	90	95	92	90	88	91	89	87	86	82			
2	1.2	2.57	5.0	101	98	96	94	99	97	95	92	96	94	92	90	93	91	89	88	84			
2.5	1.52	3.11	7.0	103	101	99	97	101	99	97	96	98	96	95	93	94	93	92	91	87			
3	1.84	3.66	10.0	104	103	101	100	102	101	100	98	99	98	97	96	96	95	94	93	89			

