

屋内照明器具特性	
品番 (品名)	NNQ37011K
光源	LED9999_70_3729.8 ×1 3729.8 1 m
管理番号	K0170240(0)DR1
BZ分類	BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	6.9	6.0	5.4	5.0	6.8	5.9	5.4	5.0	6.6	5.8	5.3	4.9	6.4	5.8	5.3	4.9	4.8
	中	0.63	0.8	7.8	7.0	6.4	6.0	7.7	6.9	6.4	6.0	7.5	6.8	6.3	5.9	7.3	6.7	6.3	5.9	5.8
	否	0.56	1.0	8.4	7.6	7.1	6.7	8.3	7.6	7.1	6.7	8.1	7.4	7.0	6.6	7.8	7.3	6.9	6.6	6.4
			1.25	8.9	8.2	7.7	7.3	8.8	8.1	7.7	7.3	8.5	8.0	7.6	7.2	8.3	7.9	7.5	7.2	7.0
下方投影面積		c m ²	1.5	9.2	8.6	8.1	7.8	9.1	8.5	8.1	7.7	8.8	8.4	8.0	7.7	8.6	8.2	7.9	7.6	7.4
等価発光面積		c m ²	2.0	9.6	9.1	8.7	8.4	9.5	9.0	8.7	8.3	9.2	8.9	8.5	8.3	9.0	8.7	8.4	8.2	8.0
取付高さ	器具間隔最大限		2.5	9.9	9.4	9.1	8.8	9.7	9.3	9.0	8.8	9.5	9.2	8.9	8.6	9.3	9.0	8.8	8.6	8.3
	横方向 (A)	縦方向 (B)	3.0	10.0	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.6
1.5m	1.33m	1.6m	4.0	10.2	9.9	9.7	9.5	10.1	9.8	9.6	9.4	9.9	9.6	9.5	9.3	9.6	9.5	9.3	9.1	8.9
2	1.76	2.09	5.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.7	10.0	9.8	9.7	9.5	9.8	9.6	9.5	9.4	9.1
2.5	2.2	2.61	7.0	10.5	10.3	10.2	10.0	10.4	10.2	10.1	9.9	10.1	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.3
3	2.65	3.14	10.0	10.6	10.5	10.4	10.3	10.5	10.4	10.3	10.2	10.2	10.1	10.1	10.0	10.0	9.9	9.9	9.8	9.5

