

屋内照明器具特性	
品番 (品名)	L G B 1 5 2 7 7 K
光源	LED3500_70_540 ×1 540.0 l m
管理番号	K0182863 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		3 % 9 7 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 9	0 . 6	5 6	4 4	3 6	3 0	5 4	4 3	3 5	3 0	5 2	4 2	3 5	3 0	4 9	4 0	3 4	3 0	2 7
			0 . 6 7	0 . 8	6 6	5 4	4 6	4 1	6 4	5 3	4 6	4 0	6 1	5 2	4 5	4 0	5 8	5 0	4 4	3 9	3 7
			0 . 6 3	1 . 0	7 2	6 2	5 4	4 8	7 1	6 1	5 3	4 8	6 7	5 9	5 2	4 7	6 4	5 7	5 1	4 7	4 4
			1 . 2 5	7 8	6 9	6 1	5 6	7 7	6 8	6 1	5 5	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 4	5 1	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 3	7 4	6 7	6 1	8 1	7 2	6 6	6 1	7 7	7 0	6 4	6 0	7 4	6 8	6 3	5 9	5 6	
			2 . 0	8 8	8 1	7 5	7 0	8 6	7 9	7 4	6 9	8 3	7 7	7 2	6 8	7 9	7 4	7 0	6 7	6 3	
取付高さ	器具間隔最大限		2 . 5	9 2	8 5	8 0	7 5	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 3	8 3	7 9	7 5	7 2	6 9	
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 9	8 4	8 0	9 2	8 7	8 3	7 9	8 9	8 4	8 1	7 7	8 5	8 2	7 9	7 6	7 2	
H m	1 . 2 8 H m 1 . 2 8 H m		4 . 0	9 7	9 3	8 9	8 5	9 6	9 1	8 8	8 4	9 2	8 9	8 5	8 3	8 9	8 6	8 3	8 1	7 7	
			5 . 0	9 9	9 6	9 2	8 9	9 8	9 4	9 1	8 8	9 4	9 1	8 9	8 6	9 1	8 8	8 6	8 4	8 1	
			7 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 3	9 2	9 0	8 8	8 5	
			1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 8	9 7	9 5	9 4	9 5	9 4	9 3	9 1	8 8	

