

# 屋内照明器具特性

品番 (品名)	XLX210UDNJ																				
光源	LED5000_85_1520 x1 1520.0 lm																				
管理番号	K0134500 (4) DB1																				
BZ分類	BZ5 / 2.3 / BZ4																				
器具効率	100%	反射率	天井 80%				70%				50%				30%			0%			
	0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	上方光束		床 10%				10%				10%				10%			0%			
	下方光束		100%	室指数																	
保守率	良	0.81	照明率 ( X0.01 )																		
	中	0.77	ZCM																		
	否	0.68	0.6	5.7	4.4	3.6	3.1	5.5	4.4	3.6	3.1	5.3	4.3	3.6	3.1	5.1	4.2	3.5	3.1	2.9	
	下方投影面積	等価発光面積	0.81	0.8	6.7	5.5	4.7	4.2	6.5	5.5	4.7	4.2	6.3	5.3	4.6	4.1	6.0	5.2	4.6	4.1	3.9
			1.25	1.5	8.4	7.5	6.8	6.3	8.2	7.4	6.8	6.3	7.9	7.2	6.7	6.2	7.6	7.0	6.6	6.1	5.9
	取付高さ	器具間隔最大限		2.0	9.0	8.2	7.6	7.2	8.8	8.1	7.6	7.1	8.5	7.9	7.4	7.0	8.2	7.7	7.3	7.0	6.7
1.5m	横方向 (A)	縦方向 (B)	2.5	9.3	8.7	8.2	7.7	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.8	7.5	7.3	
2	2.01 m	1.95 m	3.0	9.6	9.0	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.9	8.5	8.2	7.9	7.6	
2.5	2.67	2.56	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.8	8.6	9.2	8.9	8.7	8.4	8.2	
3	3.34	3.19	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.5	
	4.02	3.82	7.0	10.3	10.0	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9	
			10.0	10.5	10.3	10.1	9.9	10.3	10.2	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2	

