

# 屋内照明器具特性

品番 (品名)	LGW40100		
光源	LLD3020MLCE1 ×1	795.0 lm	
管理番号	K0176346(0)DR1		
BZ分類	BZ1		

器具効率	87%	天井	80%				70%				50%				30%				0%			
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
下方光束	87%	床	10%				10%				10%				10%				0%			
室指数	照明率 ( X0.01 )																			ZCM		
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56		
下方投影面積	cm <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0		
	等価発光面積		cm <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	
取付高さ	器具間隔最大限																					
	横方向 (A)	縦方向 (B)																				
Hm	0.41Hm	0.41Hm	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0

