

屋内照明器具特性

品番 (品名)	NNLK42590J + NNL4507HNP	
光源	LED5000_85_10400 ×1	10400.0 lm
管理番号	K0139168 (0) DB 1	
BZ分類	BZ3 / 3.5 / BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	2 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	98 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	64	54	47	42	63	53	47	42	61	52	46	42	59	51	46	42	40			
	中	0.81	0.8	73	64	57	52	72	63	57	52	69	61	56	52	67	60	55	51	49			
	否	0.77	1.0	79	70	64	59	78	69	63	59	75	68	62	58	72	66	62	58	56			
			1.25	84	76	70	66	83	75	70	65	80	74	69	65	77	72	67	64	62			
下方投影面積	c m ²		1.5	88	81	75	70	86	79	74	70	83	77	73	69	80	76	72	68	66			
	等価発光面積		c m ²	2.0	92	86	81	77	91	85	81	77	88	83	79	76	85	81	78	75	72		
取付高さ	器具間隔最大限		2.5	95	90	86	82	94	89	85	81	91	87	83	80	88	84	81	79	76			
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	96	91	88	85	93	89	86	83	90	87	84	82	79			
5 m	4.28 m	7.28 m	4.0	100	96	93	90	98	95	92	89	95	92	90	88	92	90	88	86	83			
7	6.02	10.18	5.0	101	98	96	93	100	97	94	92	97	94	92	90	94	92	90	89	86			
10	8.6	14.54	7.0	103	101	99	97	102	99	98	96	99	97	95	94	96	94	93	92	89			
15	12.9	21.81	10.0	104	103	101	100	103	101	100	99	100	99	98	96	97	96	95	94	91			

