

屋内照明器具特性	
品番 (品名)	L G C 3 1 1 5 8 K
光源	LED6200_70_3950 ×1 3950.0 lm
管理番号	K0183776 (0) D 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		4 % 96 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.63	0.6	56	44	36	30	54	43	35	30	51	41	35	30	49	40	34	29	27	
			0.6	0.8	66	54	46	40	64	53	46	40	61	51	45	39	58	50	44	39	36	
			0.56	1.0	72	61	54	48	70	60	53	47	67	58	52	47	64	56	50	46	43	
				1.25	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50	
下方投影面積		cm ²	1.5	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55		
等価発光面積			2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62		
取付高さ	器具間隔最大限			2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	71	67	
	横方向 (A)		縦方向 (B)	3.0	94	88	83	79	92	86	82	78	88	83	80	76	84	81	77	74	71	
H m	1.26 H m		1.26 H m	4.0	97	92	88	84	95	91	87	83	91	88	84	81	88	85	82	79	76	
				5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79	
				7.0	101	98	95	93	99	97	94	92	96	93	91	89	92	90	89	87	83	
				10.0	103	101	99	97	101	99	97	95	98	96	94	93	94	93	92	90	86	

