

屋内照明器具特性

品番 (品名)	NNLK41517J + NNL4600SWT	
光源	LED4000_85_6150 x1	6150.0 lm
管理番号	K0135565 (0) DB 1	
BZ分類	BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	99 %	室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.81	0.6	60	48	41	36	59	48	41	36	56	47	40	36	54	46	40	36	34			
		0.77	0.8	70	59	52	46	68	58	51	46	66	57	51	46	63	56	50	46	44			
			1.0	76	66	59	54	74	65	59	53	72	64	58	53	69	62	57	53	51			
		0.68	1.25	82	73	66	61	80	72	66	61	77	70	65	60	75	69	64	60	58			
下方投影面積	c m ²	1.5	85	77	71	66	84	76	71	66	81	75	70	65	78	73	68	65	62				
		2.0	91	84	79	74	89	83	78	74	86	81	77	73	84	79	75	72	70				
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	75			
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	83	92	88	85	82	89	86	83	81	78			
1.5m	1.47 m	2.11 m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	92	90	88	85	83			
2	1.95	2.67	5.0	101	98	95	92	99	96	94	91	97	94	92	90	94	92	90	88	86			
2.5	2.43	3.24	7.0	103	100	98	96	101	99	97	95	99	97	95	94	96	95	93	92	89			
3	2.91	3.83	10.0	104	103	101	99	103	101	100	99	100	99	98	97	98	97	96	95	92			

