

屋内照明器具特性	
品番(品名)	LGB19341BF
光源	LDA7L-D-G/S/Z6 ×3 810.0 lm
管理番号	K0126472(0)DB1
BZ分類	BZ8

器具効率	90%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	38%	反射率	床	10%				10%				10%				10%				0%
下方光束	52%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.63	0.6	41	30	23	18	38	28	21	17	32	24	18	14	27	20	16	12	8
	中	0.6	0.8	49	38	30	25	45	35	28	23	38	30	24	20	32	25	21	17	12
	否	0.56	1.0	54	43	36	30	50	40	33	28	42	35	29	24	35	29	25	21	14
			1.25	59	49	42	36	55	46	39	34	46	39	34	29	39	33	29	25	18
下方投影面積	cm ²		1.5	63	53	46	40	58	50	43	38	49	43	37	33	41	36	32	28	20
			2.0	68	60	53	47	63	56	50	45	54	48	43	39	45	40	37	33	24
等価発光面積	cm ²		2.5	71	64	58	53	66	60	54	49	57	51	47	43	48	44	40	37	27
			3.0	74	67	61	57	69	63	58	53	59	54	50	46	50	46	43	40	29
取付高さ	器具間隔最大限		4.0	77	71	67	62	72	67	62	58	62	58	54	51	52	49	47	44	33
H _m	1.54H _m	1.55H _m	5.0	79	74	70	66	74	69	66	62	64	60	57	54	54	52	49	47	35
			7.0	81	78	74	71	76	73	70	67	66	63	61	59	57	54	52	51	39
			10.0	83	81	78	75	78	76	73	71	68	66	64	62	58	57	55	54	41

