

屋内照明器具特性	
品番 (品名)	LGB15187
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0190421 (0) DR 1
B Z 分類	BZ1

器具効率		83 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		83 %																							
保守率		良	0.6	69	64	61	58	68	64	61	58	67	63	60	58	66	63	60	58	57					
		中	0.8	75	70	67	65	74	70	67	65	73	69	66	65	71	68	66	64	63					
		否	1.0	78	74	71	69	77	74	71	69	76	73	70	69	75	72	70	68	67					
			0.56	1.25	81	77	75	73	80	77	74	73	78	76	74	72	77	75	73	72	71				
下方投影面積		c m ²	1.5	82	79	77	75	82	79	77	75	80	78	76	75	79	77	75	74	73					
等価発光面積		c m ²	2.0	84	82	80	79	84	82	80	79	82	80	79	78	81	79	78	77	76					
取付 高さ	器具間隔最大限		2.5	86	84	82	81	85	83	82	81	83	82	81	80	82	81	80	79	77					
	横方向 (A)	縦方向 (B)	3.0	87	85	84	83	86	84	83	82	84	83	82	81	83	82	81	80	79					
H m	0.42 H m	0.42 H m	4.0	88	87	86	85	87	86	85	84	85	84	84	83	84	83	83	82	80					
			5.0	88	88	87	86	87	87	86	86	86	85	85	84	84	84	83	83	81					
			7.0	89	89	88	88	88	88	87	87	86	86	86	86	85	85	84	84	82					
			10.0	90	89	89	89	89	89	88	88	87	87	87	87	85	85	85	85	83					

