

屋内照明器具特性

品番 (品名)	LGB57660K															
光源	LDA7L-D-G/S/Z6 x6 810.0 lm															
管理番号	K0165036(0)D 1															
BZ分類	BZ8/0.7/BZ7															

器具効率	94%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	31% 63%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	4.4	3.2	2.4	1.9	4.1	3.0	2.3	1.8	3.6	2.7	2.0	1.6	3.1	2.3	1.8	1.4	1.0		
		0.8	5.2	4.0	3.2	2.6	4.8	3.8	3.0	2.5	4.2	3.3	2.7	2.2	3.6	2.9	2.4	2.0	1.5		
		1.0	5.7	4.6	3.8	3.1	5.4	4.3	3.6	3.0	4.7	3.8	3.2	2.7	4.0	3.3	2.8	2.4	1.8		
		1.25	6.3	5.2	4.4	3.7	5.9	4.9	4.1	3.6	5.1	4.3	3.7	3.2	4.4	3.8	3.3	2.9	2.2		
下方投影面積 等価発光面積	c m ² c m ²	1.5	6.6	5.6	4.9	4.2	6.2	5.3	4.6	4.0	5.4	4.7	4.1	3.6	4.7	4.1	3.6	3.2	2.5		
		2.0	7.2	6.3	5.6	5.0	6.8	6.0	5.3	4.7	5.9	5.3	4.7	4.3	5.2	4.7	4.2	3.8	3.0		
取付 高さ	器具間隔最大限		2.5	7.5	6.8	6.1	5.5	7.1	6.4	5.8	5.3	6.3	5.7	5.2	4.8	5.5	5.0	4.6	4.3	3.4	
	横方向 (A) H m	縦方向 (B) H m	3.0	7.8	7.1	6.5	6.0	7.4	6.7	6.2	5.7	6.5	6.0	5.5	5.1	5.7	5.3	4.9	4.6	3.7	
			4.0	8.2	7.6	7.1	6.6	7.7	7.2	6.7	6.3	6.8	6.4	6.0	5.7	6.0	5.7	5.4	5.1	4.1	
			5.0	8.4	7.9	7.4	7.0	7.9	7.5	7.1	6.7	7.1	6.7	6.3	6.0	6.2	5.9	5.7	5.4	4.4	
			7.0	8.6	8.3	7.9	7.5	8.2	7.8	7.5	7.2	7.3	7.0	6.8	6.5	6.5	6.3	6.0	5.8	4.8	
			10.0	8.9	8.6	8.3	8.0	8.4	8.1	7.9	7.6	7.5	7.3	7.1	6.9	6.7	6.5	6.4	6.2	5.2	

