

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 8
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 5 5 0 0 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 3	3 7	3 2	5 2	4 2	3 7	3 2	5 0	4 2	3 6	3 2	4 8	4 1	3 6	3 2	3 0
			0 . 6 3	0 . 8	6 2	5 4	4 8	4 3	6 1	5 3	4 7	4 3	5 9	5 2	4 7	4 3	5 7	5 1	4 6	4 3	4 1
			0 . 5 6	1 . 0	6 9	6 1	5 5	5 1	6 7	6 0	5 5	5 1	6 5	5 9	5 4	5 0	6 3	5 8	5 3	5 0	4 8
				1 . 2 5	7 4	6 7	6 2	5 8	7 2	6 6	6 1	5 8	7 0	6 5	6 1	5 7	6 8	6 3	6 0	5 7	5 5
下方投影面積 等価発光面積		c m ²	1 . 5	7 7	7 1	6 6	6 2	7 6	7 0	6 6	6 2	7 3	6 9	6 5	6 2	7 1	6 7	6 4	6 1	5 9	
			2 . 0	8 1	7 6	7 2	6 9	8 0	7 5	7 2	6 9	7 8	7 4	7 1	6 8	7 6	7 2	7 0	6 7	6 5	
			2 . 5	8 4	8 0	7 6	7 3	8 3	7 9	7 6	7 3	8 0	7 7	7 4	7 2	7 8	7 6	7 3	7 1	6 9	
取付 高さ	器具間隔最大限		3 . 0	8 5	8 2	7 9	7 6	8 4	8 1	7 8	7 6	8 2	7 9	7 7	7 5	8 0	7 8	7 6	7 4	7 2	
	横方向 (A)	縦方向 (B)		4 . 0	8 8	8 5	8 2	8 0	8 6	8 4	8 2	8 0	8 4	8 2	8 0	7 8	8 2	8 0	7 9	7 7	7 5
H m	1 . 2 8 H m	1 . 2 8 H m	5 . 0	8 9	8 7	8 5	8 3	8 8	8 6	8 4	8 2	8 6	8 4	8 2	8 1	8 4	8 2	8 1	7 9	7 7	
			7 . 0	9 0	8 9	8 7	8 6	8 9	8 8	8 6	8 5	8 7	8 6	8 5	8 3	8 5	8 4	8 3	8 2	8 0	
			1 0 . 0	9 1	9 0	8 9	8 8	9 0	8 9	8 8	8 7	8 8	8 7	8 6	8 6	8 6	8 5	8 5	8 4	8 2	

