

屋内照明器具特性

品番 (品名)	S F 2 5 1 B Z														
光源	LDA8 L - D - G - E17 / S / Z6 ×1 760.0 l m														
管理番号	K0136746 (0) DB 1														
B Z 分類	BZ10														

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30		10
上方光束	51 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	37 %		床	10 %				10 %				10 %				10 %				
室指数			照明率 (X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	3.8	2.7	2.0	1.5	3.4	2.5	1.8	1.4	2.7	2.0	1.5	1.1	2.1	1.5	1.1	0.8	0.3	
		0.8	4.5	3.4	2.7	2.2	4.1	3.1	2.4	2.0	3.2	2.5	2.0	1.6	2.4	1.9	1.5	1.2	0.5	
		1.0	5.0	4.0	3.2	2.7	4.5	3.6	2.9	2.4	3.6	2.9	2.4	1.9	2.7	2.2	1.8	1.5	0.7	
		1.25	5.5	4.5	3.8	3.2	5.0	4.1	3.4	2.9	3.9	3.3	2.8	2.3	3.0	2.5	2.1	1.8	0.9	
下方投影面積	cm ²	1.5	5.9	4.9	4.2	3.7	5.3	4.5	3.8	3.3	4.2	3.6	3.1	2.7	3.2	2.8	2.4	2.1	1.1	
等価発光面積		2.0	6.3	5.5	4.9	4.3	5.7	5.0	4.4	4.0	4.6	4.1	3.6	3.2	3.5	3.1	2.8	2.5	1.4	
取付高さ	器具間隔最大限		2.5	6.7	6.0	5.4	4.8	6.0	5.4	4.9	4.4	4.9	4.4	4.0	3.6	3.8	3.4	3.1	2.8	1.6
	横方向 (A)	縦方向 (B)	3.0	6.9	6.3	5.7	5.2	6.3	5.7	5.2	4.8	5.1	4.6	4.2	3.9	3.9	3.6	3.3	3.1	1.8
Hm	0.00Hm	0.00Hm	4.0	7.2	6.7	6.2	5.8	6.6	6.1	5.7	5.3	5.3	5.0	4.6	4.3	4.2	3.9	3.7	3.4	2.0
			5.0	7.4	6.9	6.5	6.1	6.8	6.4	6.0	5.6	5.5	5.2	4.9	4.6	4.3	4.1	3.9	3.7	2.2
			7.0	7.7	7.3	7.0	6.6	7.0	6.7	6.4	6.1	5.7	5.5	5.3	5.0	4.6	4.4	4.2	4.0	2.5
			10.0	7.9	7.6	7.3	7.1	7.2	6.9	6.7	6.5	5.9	5.7	5.6	5.4	4.7	4.6	4.4	4.3	2.7

