

屋内照明器具特性	
品番 (品名)	LGB81531BF
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 1 m
管理番号	K0128492(0)DB1
BZ分類	BZ7

器具効率	84%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	33%	床	10%				10%				10%				10%				0%	
下方光束	51%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.9	2.9	2.2	1.7	3.6	2.7	2.1	1.6	3.1	2.3	1.8	1.4	2.6	2.0	1.6	1.3	0.9
	中	0.6	0.8	4.6	3.6	2.9	2.4	4.3	3.4	2.7	2.3	3.7	2.9	2.4	2.0	3.1	2.5	2.1	1.7	1.3
	否	0.56	1.0	5.1	4.1	3.4	2.9	4.8	3.9	3.2	2.7	4.1	3.4	2.8	2.4	3.5	2.9	2.5	2.1	1.6
			1.25	5.6	4.7	4.0	3.4	5.2	4.4	3.7	3.2	4.5	3.8	3.3	2.9	3.8	3.3	2.9	2.5	1.9
下方投影面積		cm <sup>2</sup>	1.5	5.9	5.1	4.4	3.9	5.5	4.7	4.1	3.6	4.7	4.1	3.6	3.2	4.0	3.6	3.2	2.8	2.1
等価発光面積		cm <sup>2</sup>	2.0	6.4	5.6	5.0	4.5	6.0	5.3	4.7	4.3	5.2	4.6	4.2	3.8	4.4	4.0	3.6	3.3	2.5
取付高さ	器具間隔最大限		2.5	6.7	6.0	5.5	5.0	6.3	5.7	5.2	4.7	5.4	5.0	4.5	4.2	4.6	4.3	3.9	3.7	2.8
	横方向 (A)	縦方向 (B)	3.0	6.9	6.3	5.8	5.4	6.5	5.9	5.5	5.1	5.6	5.2	4.8	4.5	4.8	4.5	4.2	3.9	3.0
Hm	1.42Hm	1.43Hm	4.0	7.2	6.7	6.3	5.9	6.8	6.3	5.9	5.6	5.9	5.5	5.2	4.9	5.1	4.8	4.6	4.3	3.4
			5.0	7.4	7.0	6.6	6.2	7.0	6.6	6.2	5.9	6.1	5.8	5.5	5.2	5.3	5.0	4.8	4.6	3.6
			7.0	7.6	7.3	7.0	6.7	7.2	6.9	6.6	6.3	6.3	6.1	5.8	5.6	5.5	5.3	5.1	4.9	3.9
			10.0	7.8	7.6	7.3	7.1	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.7	5.5	5.4	5.2	4.2

