

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 9
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190532 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	49	40	34	30	48	39	34	30	46	38	33	30	44	38	33	29	28
			0.63	0.8	58	49	44	40	56	49	44	40	54	48	43	39	53	47	43	39	38
			0.56	1.0	63	56	51	47	62	55	50	47	60	54	50	46	58	53	49	46	45
				1.25	68	62	57	53	67	61	57	53	65	60	56	53	63	59	55	52	51
下方投影面積 等価発光面積		c m ² c m ²		1.5	71	65	61	58	70	65	61	57	68	63	60	57	66	62	59	56	55
				2.0	75	70	67	64	74	70	66	63	72	68	65	63	70	67	64	62	60
				2.5	77	74	70	68	76	73	70	67	74	71	69	66	72	70	68	66	64
				3.0	79	76	73	70	78	75	72	70	76	73	71	69	74	72	70	68	66
H m	1.27 H m	1.27 H m		4.0	81	78	76	74	80	78	75	74	78	76	74	73	76	74	73	71	70
				5.0	82	80	78	76	81	79	77	76	79	78	76	75	77	76	75	74	71
				7.0	83	82	81	79	82	81	80	79	81	79	78	77	79	78	77	76	74
				10.0	84	83	82	81	83	82	82	81	82	81	80	79	80	79	78	78	76

