

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 8 1 W F
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 5 9 3 8 (0) D R 1
B Z 分類	B Z 7 / 4 . 5 / B Z 6 / 6 . 0 / B Z 7 / 8 . 5 / B Z 6

器具効率	69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	33 %	室指数	床	10 %				10 %				10 %				10 %				0 %	
下方光束	36 %		照明率 (X 0 . 0 1)																Z C M		
保守率	良 0.63	0.6 中 否 0.56	0.6	3.2	2.4	1.8	1.4	2.9	2.2	1.7	1.4	2.5	1.9	1.5	1.2	2.0	1.5	1.2	1.0	6	
	0.8		3.8	3.0	2.4	2.0	3.5	2.8	2.2	1.9	2.9	2.3	1.9	1.6	2.4	2.0	1.6	1.4	9		
	1.0		4.2	3.4	2.9	2.4	3.9	3.2	2.7	2.3	3.2	2.7	2.3	2.0	2.7	2.3	1.9	1.7	1.2		
	1.25		4.6	3.9	3.3	2.9	4.2	3.6	3.1	2.7	3.5	3.0	2.7	2.3	2.9	2.5	2.2	2.0	1.4		
下方投影面積	cm ²	等価発光面積	cm ²	1.5	4.8	4.2	3.7	3.2	4.5	3.9	3.4	3.0	3.8	3.3	2.9	2.6	3.1	2.8	2.5	2.2	1.6
				2.0	5.2	4.7	4.2	3.8	4.8	4.3	3.9	3.5	4.1	3.7	3.4	3.1	3.4	3.1	2.8	2.6	1.9
取付高さ	器具間隔最大限		2.5	5.5	5.0	4.5	4.2	5.1	4.6	4.2	3.9	4.3	4.0	3.7	3.4	3.6	3.3	3.1	2.9	2.1	
	横方向 (A)	縦方向 (B)	3.0	5.7	5.2	4.8	4.5	5.2	4.8	4.5	4.2	4.5	4.1	3.9	3.6	3.7	3.5	3.3	3.1	2.2	
H m	1.29 H m	1.72 H m	4.0	5.9	5.5	5.2	4.9	5.5	5.1	4.8	4.6	4.7	4.4	4.2	4.0	3.9	3.7	3.5	3.4	2.5	
			5.0	6.0	5.7	5.4	5.2	5.6	5.3	5.1	4.8	4.8	4.6	4.4	4.2	4.0	3.9	3.7	3.6	2.6	
			7.0	6.2	6.0	5.7	5.5	5.8	5.6	5.4	5.2	5.0	4.8	4.6	4.5	4.2	4.1	3.9	3.8	2.8	
			10.0	6.3	6.2	6.0	5.8	5.9	5.7	5.6	5.4	5.1	5.0	4.8	4.7	4.3	4.2	4.1	4.0	3.0	

