

# 屋内照明器具特性

品番 (品名)	L G W J 5 6 0 0 0 F																
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m																
管理番号	K0175942 ( 0 ) DR 1																
BZ分類	BZ10																

器具効率	59 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	32 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	27 %		室指数																	
保守率	良 中 否 0.63 0.6 0.56	照明率 ( X0.01 ) ZCM																		
		0.6	25	17	13	9	23	16	11	8	18	13	9	7	14	10	7	5	2	
		0.8	30	22	17	13	27	20	15	12	21	16	12	10	16	12	9	7	3	
		1.0	33	26	21	17	30	23	19	15	24	19	15	12	18	14	12	9	4	
		1.25	36	29	24	20	33	27	22	18	26	21	18	15	20	17	14	11	6	
下方投影面積	c m <sup>2</sup>	1.5	39	32	27	23	35	29	25	21	28	24	20	17	22	18	16	13	7	
等価発光面積		c m <sup>2</sup>	2.0	42	36	32	28	38	33	29	26	31	27	24	21	24	21	19	16	9
取付高さ	器具間隔最大限		2.5	44	39	35	31	40	36	32	29	33	29	26	24	26	23	21	19	11
	横方向 ( A )	縦方向 ( B )	3.0	46	41	37	34	42	38	34	31	34	31	28	26	27	25	22	20	12
H m	0.00 H m	0.00 H m	4.0	48	44	41	38	44	41	38	35	36	33	31	29	29	27	25	23	14
			5.0	49	46	43	40	45	42	40	37	37	35	33	31	30	28	26	25	16
			7.0	51	49	46	44	47	45	43	40	39	37	35	34	31	30	29	27	18
			10.0	53	51	49	47	48	47	45	43	40	39	38	36	33	32	31	30	20

