

屋内照明器具特性

品番 (品名)	NCN19302S	
光源	LED3500_85_1650 ×1	1650.0lm
管理番号	K0177435(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	101%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	80	73	68	65	79	72	68	65	77	72	68	65	76	71	67	65	63
	中	0.77	0.8	87	81	77	74	86	81	77	74	85	80	76	73	83	79	76	73	72
	否	0.68	1.0	92	86	82	79	91	86	82	79	89	85	81	79	87	84	81	79	77
下方投影面積	cm ²		1.25	95	91	87	84	94	90	87	84	93	89	86	84	91	88	85	83	82
			1.5	98	94	90	88	97	93	90	87	95	92	89	87	93	90	88	86	84
等価発光面積	cm ²		2.0	101	97	95	92	100	96	94	92	98	95	93	91	96	94	92	90	88
			2.5	102	100	97	95	101	99	96	95	99	97	95	94	97	95	94	93	91
取付高さ	器具間隔最大限		3.0	104	101	99	97	102	100	98	97	100	98	97	95	98	97	95	94	92
	横方向 (A)	縦方向 (B)	4.0	105	103	101	100	104	102	100	99	102	100	99	98	100	98	97	96	94
Hm	0.64Hm	0.64Hm	5.0	106	104	103	101	105	103	102	101	102	101	100	99	100	99	99	98	95
			7.0	107	105	104	103	105	104	103	103	102	102	101	101	101	100	99	99	97
			10.0	107	107	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98

