

屋内照明器具特性

品番 (品名)	L G W C 8 1 3 3 7 K				
光源	LED5000_70_225 x1 225.0 l m				
管理番号	K0160249 (0) DR 1				
B Z 分類	B Z 9				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	50 %	室指数																	照明率 (X 0.01)																	Z C M																
下方光束	50 %																																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	45	32	24	19	41	30	22	17	33	25	19	14	27	20	15	11	6																														
		0.6	0.6	0.6	0.6	53	41	32	26	48	37	30	24	39	31	25	20	32	25	20	16	10																														
		0.56	0.56	0.56	0.56	59	47	38	32	53	43	35	29	44	36	30	25	35	29	24	20	12																														
		0.56	0.56	0.56	0.56	64	53	45	38	59	49	41	35	48	40	34	30	39	33	28	24	15																														
下方投影面積	c m ²	1.25	1.5	2.0	2.5	64	53	45	38	59	49	41	35	48	40	34	30	39	33	28	24	15																														
		1.5	2.0	2.5	3.0	68	58	50	43	62	53	46	40	51	44	38	34	41	36	31	27	17																														
等価発光面積	c m ²	2.0	2.5	3.0	4.0	74	65	57	51	68	59	53	47	56	50	44	40	45	40	36	33	21																														
		2.5	3.0	4.0	5.0	77	69	62	56	71	64	58	52	59	53	49	44	48	44	40	37	24																														
取付高さ	器具間隔最大限		H m	1.07 H m	1.52 H m	3.0	4.0	5.0	7.0	8.0	8.3	7.7	7.2	6.7	7.7	7.2	6.7	6.2	6.5	6.0	5.7	5.3	5.3	5.0	4.7	4.4	3.0																									
	横方向 (A)	縦方向 (B)				4.0	5.0	7.0	8.0	8.3	7.7	7.2	6.7	7.7	7.2	6.7	6.2	6.5	6.0	5.7	5.3	5.3	5.0	4.7	4.4	3.0																										
						5.0	7.0	8.0	8.3	8.6	8.1	7.6	7.1	7.9	7.5	7.0	6.6	6.7	6.3	6.0	5.7	5.5	5.2	4.9	4.7	3.2																										
						7.0	8.0	8.3	8.8	8.8	8.4	8.1	7.7	8.2	7.8	7.5	7.2	6.9	6.6	6.4	6.1	5.7	5.5	5.3	5.1	3.6																										
						10.0	10.0	9.1	8.8	8.5	8.2	8.4	8.1	7.9	7.6	7.1	6.9	6.7	6.5	6.5	5.9	5.8	5.6	5.4	3.9																											

