

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 8 7
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 5 4 9 3 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 5	4 5	3 8	3 4	5 4	4 4	3 8	3 4	5 2	4 3	3 8	3 3	5 0	4 2	3 7	3 3	3 2
			0 . 6 3	0 . 8	6 5	5 6	4 9	4 5	6 4	5 5	4 9	4 5	6 1	5 4	4 9	4 4	5 9	5 3	4 8	4 4	4 3
			0 . 5 6	1 . 0	7 1	6 3	5 7	5 3	7 0	6 2	5 7	5 3	6 8	6 1	5 6	5 2	6 6	6 0	5 6	5 2	5 0
			1 . 2 5	7 7	7 0	6 4	6 0	7 5	6 9	6 4	6 0	7 3	6 7	6 3	5 9	7 1	6 6	6 2	5 9	5 7	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 0	7 4	6 9	6 5	7 9	7 3	6 8	6 5	7 7	7 1	6 7	6 4	7 4	7 0	6 6	6 3	6 2	
			2 . 0	8 5	7 9	7 5	7 2	8 3	7 9	7 5	7 1	8 1	7 7	7 4	7 1	7 9	7 5	7 2	7 0	6 8	
			2 . 5	8 7	8 3	7 9	7 6	8 6	8 2	7 9	7 6	8 4	8 0	7 7	7 5	8 2	7 9	7 6	7 4	7 2	
取付 高さ	器具間隔最大限		3 . 0	8 9	8 5	8 2	7 9	8 8	8 4	8 1	7 9	8 6	8 3	8 0	7 8	8 3	8 1	7 9	7 7	7 5	
	横方向 (A)	縦方向 (B)	4 . 0	9 1	8 8	8 6	8 4	9 0	8 7	8 5	8 3	8 8	8 6	8 4	8 2	8 6	8 4	8 2	8 1	7 8	
H m	1 . 2 7 H m	1 . 2 7 H m	5 . 0	9 3	9 0	8 8	8 6	9 1	8 9	8 7	8 5	8 9	8 7	8 6	8 4	8 7	8 6	8 4	8 3	8 1	
			7 . 0	9 4	9 2	9 1	8 9	9 3	9 1	9 0	8 8	9 1	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 3	
			1 0 . 0	9 5	9 4	9 3	9 2	9 4	9 3	9 2	9 1	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 8	8 5	

