

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 8 7
光源	L L D 4 0 4 0 2 C Q 1 (K A K U S A N) × 1 8 6 0 . 0 1 m
管理番号	K 0 1 8 5 5 0 2 (0) D R 1
B Z 分類	B Z 3 / 1 . 1 / B Z 2

器具効率		9 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 8	4 2	3 7	5 7	4 8	4 1	3 7	5 5	4 7	4 1	3 7	5 3	4 6	4 1	3 7	3 5
			0 . 6 3	0 . 8	6 8	6 0	5 4	4 9	6 7	5 9	5 3	4 9	6 5	5 8	5 3	4 9	6 3	5 7	5 2	4 9	4 7
			0 . 5 6	1 . 0	7 5	6 7	6 2	5 7	7 4	6 6	6 1	5 7	7 1	6 5	6 0	5 7	6 9	6 4	6 0	5 7	5 5
				1 . 2 5	8 0	7 3	6 8	6 4	7 9	7 3	6 8	6 4	7 7	7 1	6 7	6 4	7 5	7 0	6 6	6 3	6 2
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 3	7 7	7 3	6 9	8 2	7 7	7 2	6 9	8 0	7 5	7 1	6 8	7 8	7 4	7 1	6 8	6 6	
			2 . 0	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 5	8 4	8 0	7 7	7 5	8 2	7 9	7 6	7 4	7 2	
			2 . 5	9 0	8 6	8 3	8 0	8 9	8 5	8 2	7 9	8 7	8 4	8 1	7 9	8 5	8 2	8 0	7 8	7 6	
取付 高さ	器具間隔最大限		3 . 0	9 2	8 8	8 5	8 3	9 1	8 7	8 5	8 2	8 8	8 6	8 3	8 1	8 6	8 4	8 2	8 0	7 8	
	横方向 (A)	縦方向 (B)		9 4	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 0	8 8	8 7	8 5	8 8	8 7	8 5	8 4	8 1	
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	9 4	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 0	8 8	8 7	8 5	8 8	8 7	8 5	8 4	8 1	
			5 . 0	9 5	9 3	9 1	8 9	9 4	9 2	9 0	8 8	9 2	9 0	8 9	8 7	9 0	8 8	8 7	8 6	8 3	
			7 . 0	9 6	9 5	9 3	9 2	9 5	9 4	9 2	9 1	9 3	9 2	9 1	9 0	9 1	9 0	8 9	8 8	8 6	
			1 0 . 0	9 7	9 6	9 5	9 4	9 6	9 5	9 4	9 3	9 4	9 3	9 2	9 2	9 2	9 1	9 1	9 0	8 8	

