

屋内照明器具特性	
品番 (品名)	NYM20171K
光源	LED5000_85_16000 ×1 16000.0 1 m
管理番号	K0172770 (4) DR 1
BZ分類	BZ1 / 1.1 / BZ2

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	99 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否 0.83 0.81 0.77	0.6	73	64	59	55	72	64	59	55	70	63	58	55	68	62	58	55	53				
		0.8	81	73	67	63	79	72	67	63	77	71	66	63	75	70	66	63	61				
		1.0	85	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	66				
		1.25	90	83	78	75	88	82	78	74	86	81	77	74	84	79	76	73	71				
下方投影面積	c m <sup>2</sup>	1.5	92	87	82	79	91	86	82	78	89	84	80	77	86	83	79	77	75				
		2.0	96	91	87	84	95	90	87	84	92	89	85	83	90	87	84	82	80				
取付高さ	器具間隔最大限		2.5	99	94	91	88	97	93	90	87	95	91	89	86	92	89	87	85	83			
	横方向 (A)	縦方向 (B)	3.0	100	97	93	91	99	95	93	90	96	93	91	89	94	91	89	88	85			
H m	0.84 H m	0.84 H m	4.0	102	99	97	94	101	98	96	94	98	96	94	92	96	94	92	91	88			
			5.0	103	101	99	97	102	100	98	96	99	98	96	94	97	95	94	93	90			
			7.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92			
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	99	99	98	97	94			

