

屋内照明器具特性	
品番 (品名)	XLGB1408
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0182819 (0) DB1
BZ分類	BZ4/0.7/BZ3

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01)																Z	CM	
保守率		良 中 否	0.67	0.6	49	40	34	30	48	40	34	30	46	39	34	30	45	38	33	30	28		
			0.63	0.8	58	50	44	40	57	49	44	40	55	48	44	40	53	47	43	40	38		
			0.56	1.0	64	57	51	47	63	56	51	47	61	55	50	47	59	54	50	47	45		
				1.25	69	62	58	54	68	62	57	54	66	61	57	53	64	59	56	53	51		
下方投影面積 等価発光面積		cm ²		1.5	72	66	62	58	71	66	61	58	69	64	61	58	67	63	60	57	55		
				2.0	76	71	68	64	75	71	67	64	73	69	66	63	71	68	65	63	61		
				2.5	78	75	71	68	77	74	71	68	75	72	70	67	73	71	68	66	65		
				3.0	80	77	74	71	79	76	73	71	77	74	72	70	75	73	71	69	67		
H	m	1.28 H	m	1.28 H	m	4.0	82	79	77	75	81	79	76	74	79	77	75	73	77	75	74	72	70
						5.0	83	81	79	77	82	80	78	77	80	78	77	76	78	77	76	74	72
						7.0	85	83	81	80	83	82	81	79	82	80	79	78	80	79	78	77	75
						10.0	86	84	83	82	84	83	82	82	83	82	81	80	81	80	79	79	76

