

屋内照明器具特性

品番 (品名)	NNLK42764J + NNFK42260J + NE	
光源	LED3000_85_2470 x1 2470.0 lm	
管理番号	K0192938 (0) DB 1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	100 %		室指数	照明率 (X0.01)																			
保守率	良 中 否	0.77	0.6	5.7	4.5	3.7	3.2	5.6	4.5	3.7	3.2	5.4	4.3	3.7	3.2	5.1	4.2	3.6	3.2	3.0			
		0.72	0.8	6.7	5.6	4.8	4.3	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.1	5.3	4.7	4.2	4.0			
		0.68	1.0	7.4	6.3	5.6	5.0	7.2	6.3	5.5	5.0	7.0	6.1	5.5	5.0	6.7	5.9	5.4	4.9	4.7			
			1.25	8.0	7.0	6.3	5.8	7.8	6.9	6.3	5.7	7.5	6.8	6.2	5.7	7.3	6.6	6.1	5.6	5.4			
下方投影面積	c m ²	1.5	8.4	7.5	6.9	6.3	8.2	7.4	6.8	6.3	7.9	7.2	6.7	6.2	7.7	7.1	6.6	6.2	5.9				
		2.0	9.0	8.2	7.7	7.2	8.8	8.1	7.6	7.1	8.5	7.9	7.4	7.0	8.2	7.7	7.3	7.0	6.7				
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.7	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.8	7.5	7.2			
	横方向 (A)	縦方向 (B)	3.0	9.6	9.0	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.6			
1.5m	1.9m	2.15m	4.0	9.9	9.4	9.1	8.7	9.7	9.3	9.0	8.7	9.4	9.1	8.8	8.5	9.2	8.9	8.6	8.4	8.1			
2	2.51	2.71	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.9	9.4	9.1	8.9	8.7	8.5			
2.5	3.12	3.3	7.0	10.3	10.0	9.8	9.5	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.1	8.9			
3	3.73	3.89	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.6	9.8	9.7	9.6	9.5	9.2			

